



HEAVY LOADS HAVE MET THEIR MATCH.

THE BOBCAT BBC23S-7 BURDEN CARRIER

The Bobcat® BBC23S-7 burden carrier is engineered to move heavy materials efficiently and safely through manufacturing and warehouse settings. Designed with a durable steel deck, pneumatic tires and an adjustable tilt steering column, it's made to transport cargo up to 4,400 pounds while providing an effortlessly smooth ride.

48-Volt Curtis Controller

The reliable 48-volt Curtis® controller is an industry standard, providing smooth power and energy efficiency while being easy to diagnose.

Lighting Package

A standard light package improves visibility and includes a directional indicator and backup light for safety.

Easily Removable Steel Deck

The steel cargo deck is easily removable for maintenance needs. Convenient handholds allow for quick access to the inner battery compartment.

Passenger Seat

The ergonomically designed seat increases comfort and productivity.

Dual Braking System

A dual braking system gives you the stopping power required for heavy loads.

Power Steering

Standard power steering makes driving effortless for the operator.

Tilt Steering Column

The tilt steering column adjusts to comfortably fit any size operator.

Pneumatic Tires

Pneumatic tires provide essential traction and a comfortable ride.

Amber Strobe

An optional amber strobe makes everyone aware of the vehicle's presence.

Side Deck Rails and Rear Gate

Optional side rails and rear tailgate help contain large loads.

SPECIFICATIONS	BBC23S-7
Capacity	4400 lb. (2000 kg)
Battery Voltage	48V (330 Ah)
Battery Compartment Size	29.0 x 16.0 x 19.0 in. (740 x 426 x 505 mm)
Drive Motor Power	4.0 hp (3.0 kW)
Operation Type	Hydraulic
Travel Speed: Loaded/Unloaded	6.8 mph (11.0 km/hr.) / 8.0 mph (13 km/hr.)
Gradeability: Loaded/Unloaded	10% / 20%
Tires	Pneumatic
Tire Size (Front)	6.00-9-10 Pr
Tire Size (Rear)	6.50-10-10 Pr
Wheels, Load/Caster (x=Drive)	2/2x
Tread (Front)	42.5 in. (1080 mm)
Tread (Rear)	42.1 in. (1070 mm)
Service Weight (With Battery)	3200 lb. (1450 kg)
Axle Loading: Loaded (Front/Rear)	2345 lb. (1104 kg) / 5172 lb. (2346 kg)
Axle Loading: Unloaded (Front/Rear)	1490 lb. (676 kg) / 1706 lb. (774 kg)
Overall Height	50.3 in. (1280 mm)
Seat Height/Stand Height	31.5 in. (800 mm)
Coupling Height	19.7 in. (500 mm)
Loading Height: Unloaded	29.5 in. (750 mm)
Overhang	24.8 in. (630 mm)
Wheelbase	63.0 in. (1600 mm)
Overall Length	126.0 in. (3200 mm)
Width of Loading Surface	49.2 in. (1250 mm)
Overall Width	49.2 in. (1250 mm)
Ground Clearance	4.7 in. (120 mm)
Outside Turning Radius	126.0 in. (3200 mm)
Internal Turning Radius	55.0 in. (1400 mm)

For more information on model details, go to [Bobcat.com](https://www.bobcat.com)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2024 Bobcat Company. All rights reserved.



B-3084 (04/24)
EP-2M-0424-10011-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
[Bobcat.com](https://www.bobcat.com)



Bobcat®

One Tough Animal.